



Proximity Effects in a Chemically Amplified Electron Beam Resist Patterned at 100 keV

Tiddi, William; Greibe, Tine; Beleggia, Marco; Han, Anpan

Published in:

Book of Abstracts. DTU's Sustain Conference 2015

Publication date:

2015

Document Version

Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):

Tiddi, W., Greibe, T., Beleggia, M., & Han, A. (2015). Proximity Effects in a Chemically Amplified Electron Beam Resist Patterned at 100 keV. In *Book of Abstracts. DTU's Sustain Conference 2015* [P-12] Technical University of Denmark.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Proximity Effects in a Chemically Amplified Electron Beam Resist Patterned at 100 keV

W. Tiddi^{1,2*}, T. Greibe¹, M. Beleggia², A. Han¹

1: DTU Danchip; 2: DTU CEN

*wiltid@dtu.dk

Electron beam lithography (EBL) is a patterning technique providing nanometric resolution. It is widely used in research, optical and nanoimprint lithography mask production, and parallel EBL is intended to be adopted in future next generation high through-put semiconductor device production [1]. Sub-20 nm patterning has been demonstrated on negative tone, epoxy-based chemically amplified EBL resists such as mr-EBL 6000 [2]. This material is characterized by significantly reduced dose sensitivity, which would provide faster, more cost-effective production.

When distances between structures are comparable to the intended critical (smallest) feature dimension, proximity effects (PE) caused by forward and back scattered electrons deteriorate the quality of the resulting pattern. PE on mr-EBL 6000 were observed when patterning with 10 and 20 keV electron beams, and compensated through dose modulation algorithms [3]. The present investigation focused instead on PE in mr-EBL at substantially higher electron energy and is to our knowledge new. To understand these conditions and their expected profound influence on PE, we patterned carefully arranged structures at 100 keV, and transferred them into a silicon substrate by reactive ion etching (RIE). We successfully patterned 50 to 500 nm wide lines, and we observed pattern deterioration when feature separation approached 5 times the line width (Fig. 1). We attribute this to PE. As a simple optimization, we showed how under-dosed patterns offer appreciable improvements in minimum obtainable pitch, and obtained analogous results in films thinner than 40 nm, an expected mandatory requirement to push manufacturing towards sub-10 nm half-pitch resolution [4].

[1] G. de Boer et al., Proc. Of SPIE 8680 (2013) 86800O-12.

[2] B. Bilenberg et al., J. Vac. Sci. Technol. B 24 (2006) 1776.

[3] G. Rius, E-beam litho. for Nanofabrication, Ph.D. Thesis, Dept. of Phys., Uni. Autò. Barcelona, 2008.

[4] A. Tavakkoli K. G. et al., J. Vac. Sci. Technol. B 29 (2011) 011035.




Figure 1 – Cross sectional SEM image of progressively closer spaced lines patterned in resist (a) and transferred into silicon through RIE (b). We observe overexposure in denser patterns because of PE; the resulting distorted pattern is this way reproduced into the underlying substrate.